

Ditch Tiling Policy - Village of Teutopolis

- 1. Tile material must be concrete, corrugated steel or double wall PVC. PVC tiles, if used, shall have a minimum of one (1) foot cover.**
- 2. Minimum tile size shall be twelve (12) inches.**
- 3. There must be enough cover over the pipe so as a swell or dip can be formed to allow storm water from the road to drain in the culvert and not flow down side of roadway. If this cannot be accomplished the request shall be denied.**
- 4. Catch basins shall be located at each property line and at any low spot. The catch basin must be a manufactured "tee" or constructed of block/brick and must have a concrete floor so no washing our or undermining can occur. The size of the catch basin shall be sufficient to the anticipated water shed and shall be subject to Village approval.**
- 5. The tiling of any ditch requires approval from the Village Board and Village Foreman. In the event the Village deems it necessary to solicit the services and or opinions of their Engineers the cost associated with the same shall be at the expense of the property owner.**
- 6. The property owner wanting the ditch tiled will incur all expenses. This includes (but not limited to) the tile, piping, dirt, catch basins, equipment, labor, sand and engineering.**
- 7. Prior to final installation and covering of the tile the property owner must notify the Village Foreman who must inspect the project. If this is not done, the Village, at the homeowner's expense, will remove any unauthorized tiling of the ditch.**

I have read the above procedures on tiling of ditches and agree to abide by the policy set forth by the Village Board of the Village of Teutopolis.

Applicant: _____

Date: _____

Village Foreman: _____

Date: _____